

View Online at <https://aerobasegroup.com/nsn/5320-01-016-7575>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.823 inches and 0.843 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2485 inches and 0.2495 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.5018 inches and 0.5066 inches

Lubrication:

Cetyl alcohol

Grip Length:

0.443 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

210000 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

125000 single pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Steel comp 431

Material Specification:

Mil-s-18732 military specification single material response or ams 5628 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.