# NSN 5320-01-016-8119

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-016-8119

## Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

## Shank Diameter:

Between 0.213 inches and 0.215 inches

## Shank Style:

Threaded self-plugging shank w/sleeve

# Head Major Diameter:

0.342 inches

#### **Expansion Device:**

Threaded stem

#### Lubrication:

Cetyl alcohol or dry film

#### Grip Length:

Between 0.845 inches and 0.906 inches

#### Min. Tensile Strength (psi):

2100 pounds per square inch

#### Hardness Rating:

48.0 rockwell c stem and 53.0 rockwell c stem

#### Shear Strength:

6900 double pounds per square inch

# Countersink Angle:

100.0 degrees

Material:

Steel comp h11 stem

#### **Material Specification:**

Ams 6487 assn standard single material response stem

#### Surface Treatment:

Cadmium stem

#### Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response sleeve

#### Shelf Life:

N/a

# Unit Of Measure:

--

#### Demilitarization:

No

# Fiig:

A040a0