NSN 5320-01-017-0171

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-017-0171

View Online at https://aerobasegroup.com/nsn/5320-01-017-0171
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.178 inches and 0.180 inches
Shank Style:
Threaded self-plugging shank w/sleeve
Head Major Diameter:
Between 0.296 inches and 0.332 inches
Expansion Device:
Threaded stem
Lubrication:
Cetyl alcohol or dry film
Grip Length:
0.438 inches
Min. Tensile Strength (psi):
1350 pounds per square inch
Hardness Rating:
48.0 rockwell c stem and 53.0 rockwell c stem
Shear Strength:
4680 double pounds per square inch
Countersink Angle:
100.0 degrees
Material:
Steel sleeve
Material Specification:
Asm 6487 assn standard single material response body
Surface Treatment:
Cadmium stem
Surface Treatment Specification:
Qq-p-416, type 1, cl 3 federal specification single treatment response sleeve
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:

Ŭ

A040a0