## NSN 5320-01-019-2476

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-019-2476

Fastener Length:
0.513 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.155 inches and 0.159 inches
Shank Style:
Self-plugging mechanically locked stem
Head Major Diameter:
Between 0.272 inches and 0.280 inches
Expansion Device:
Serrated stem-type w
Grip Length:
Between 0.313 inches and 0.375 inches
Shear Strength:
755 single pounds per square inch
Countersink Angle:
100.0 degrees
Heat Treatment:
H-38 strain hardened locking ring
Material:
Aluminum alloy 5056 locking ring
Material Specification:
Qq-a-430 federal specification single material response locking ring
Surface Treatment:
Anodize body
Surface Treatment Specification:
Mil-c-5541 military specification single treatment response stem
Specification Data:
80205-nas1399 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
<u></u>
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
Mil-a-8625 spec

Mil-a-8625 spec.