NSN 5320-01-019-3800

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-019-3800 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.697 inches and 0.717 inches **Head Style:** Err-090 **Head Height:** Between 0.080 inches and 0.090 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.415 inches and 0.440 inches Lubrication: Cetyl alcohol **Grip Length:** 0.317 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 95000 single pounds per square inch Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** 294, fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

NSN 5320-01-019-3800

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0