## NSN 5320-01-019-6882

No Fiig: A040a0



Tubular Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-01-019-6882 **Fastener Length:** 0.469 inches **Head Style: Button Head Height:** Between 0.080 inches and 0.088 inches **Hole Diameter:** Between 0.084 inches and 0.090 inches **Shank Diameter:** Between 0.118 inches and 0.128 inches **Shank Style:** Tubular **Head Major Diameter:** Between 0.218 inches and 0.228 inches **Hole Depth:** 0.094 inches **Grip Length:** 0.375 inches **Shear Strength:** 32000 double pounds per square inch Material: Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 **Material Specification:** 66 comp c1005-c1022 federal standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Specification Or Standard:** 12 type and 3 class and e grade Shelf Life: N/a **Unit Of Measure: Demilitarization:**