## NSN 5320-01-019-8931

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-019-8931

view Offilite at https://aerobasegroup.com/hish/5525-01-015-0551
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.274 inches and 0.276 inches
Shank Style:
Threaded self-plugging shank w/sleeve
Head Major Diameter:
0.463 inches
Expansion Device:
Threaded stem
Lubrication:
Cetyl alcohol or dry film
Grip Length:
Between 0.157 inches and 0.219 inches
Min. Tensile Strength (psi):
3650 pounds per square inch
Hardness Rating:
48.0 rockwell c stem and 53.0 rockwell c stem
Shear Strength:
11800 double pounds per square inch
Countersink Angle:
100.0 degrees
Material:
Steel comp h11 stem
Material Specification:
Ams 6487 assn standard single material response stem
Surface Treatment:
Cadmium stem
Surface Treatment Specification:
Qq-p-416, type 1, cl 3 federal specification single treatment response sleeve
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiio:

A040a0