NSN 5320-01-021-2336

Fiig: A040a0

Mil-std (military Standard):

Mil-s-6758 spec.



Blind Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-01-021-2336 Fastener Length: 1.186 inches **Head Style:** Hexagon **Head Height:** 0.113 inches **Shank Diameter:** Between 0.202 inches and 0.203 inches **Shank Style:** Threaded self-plugging shank w/sleeve **Expansion Device:** Threaded stem Lubrication: Grease film **Grip Length:** Between 0.396 inches and 0.436 inches Width Across Flats: Between 0.305 inches and 0.312 inches Hardness Rating: 39.0 rockwell c and 45.0 rockwell c **Shear Strength:** 5240 double pounds per square inch Material: Steel comp 4130 body or steel comp 4140 body or steel comp 8740 body **Material Specification:** Qq-s-763 federal specification 1st material response sleeve or qq-s-763 federal specification 2nd material response sleeve or ams 5639 assn standard 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve **Surface Treatment:** Cadmium stem **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response stem Shelf Life: N/a **Unit Of Measure:** Demilitarization: No