## NSN 5320-01-022-3854

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-022-3854

| Fastener Length:   |
|--|
| Between 0.615 inches and 0.635 inches  |
| Head Style:  |
| Undersized oval countersunk  |
| Head Height:   |
| Between 0.004 inches and 0.006 inches  |
| Shank Diameter:  |
| Between 0.249 inches and 0.252 inches  |
| Shank Style:   |
| Straight   |
| Head Major Diameter:   |
| Between 0.3710 inches and 0.3948 inches  |
| Head Minor Diameter:   |
| Between 0.316 inches and 0.326 inches  |
| Countersink Height:  |
| 0.060 inches   |
| Shear Strength:  |
| 24000 single pounds per square inch  |
| Countersink Angle:   |
| 100.0 degrees  |
| Material:  |
| Aluminum alloy 5056  |
| Material Specification:  |
| Qq-a-430 federal specification single material response  |
| Surface Treatment:   |
| Anodize or chromate  |
| Surface Treatment Specification:   |
| Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response |
| Specification Data:  |
| 80205-nas1097 professional/industrial association standard   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A040a0   |
| Mil-std (military Standard):   |
| Mil-a-8625 spec.   |