NSN 5320-01-022-5635



Blind Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-01-022-5635 **Thread Class:** 3b **Thread Direction:** Right-hand **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.335 inches and 0.338 inches **Shank Style:** Blind rivet, nut and bolt (assembly) **Head Major Diameter:** 0.530 inches **Expansion Device:** Threaded sleeve **Grip Length:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.216 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp 305 sleeve or steel comp 302 sleeve or steel sleeve **Material Specification:** Qq-s-763 federal specification 1st material response sleeve or astm a493 assn standard 2nd material response sleeve or astm a493 comp 18-9 lw assn standard 3rd material response sleeve **Surface Treatment:** Passivate sleeve **Surface Treatment Specification:** Qq-p-416, type 1, cl 2 federal specification single treatment response expander **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:
-Demilitarization:
No
Fiig:
A040a0