NSN 5320-01-022-5635

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-022-5635

Thread Class:

3b

Thread Direction:

Right-hand

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.335 inches and 0.338 inches

Shank Style:

Blind rivet, nut and bolt (assembly)

Head Major Diameter:

0.530 inches

Expansion Device:

Threaded sleeve

Grip Length:

0.250 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.216 inches

Shear Strength:

125000 single pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Steel comp 305 sleeve or steel comp 302 sleeve or steel sleeve

Material Specification:

Qq-s-763 federal specification 1st material response sleeve or astm a493 assn standard 2nd material response sleeve or astm a493 comp

18-9 lw assn standard 3rd material response sleeve

Surface Treatment:

Passivate sleeve

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response expander

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A040a0