## NSN 5320-01-022-8157

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-022-8157

view Offilite at https://aerobasegroup.com/hsh/3520-01-022-
Fastener Length:
Between 0.490 inches and 0.510 inches
Head Style:
Undersized oval countersunk
Head Height:
Between 0.003 inches and 0.005 inches
Shank Diameter:
Between 0.124 inches and 0.127 inches
Shank Style:
Straight
Head Major Diameter:
Between 0.174 inches and 0.196 inches
Head Minor Diameter:
Between 0.134 inches and 0.144 inches
Countersink Height:
0.029 inches
Shear Strength:
468 single pounds per square inch
Countersink Angle:
100.0 degrees
Heat Treatment:
T-73 solution heat treated
Material:
Aluminum alloy 7050
Material Specification:
Qq-a-430 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-c-5541 military specification single treatment response
Specification Data:
80205-nas1097 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-c-5541 spec.

Mil-std (military Standard):

A040a0