NSN 5320-01-024-3399

Solid Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-024-3399

view Online at https://aerobasegroup.com/hsh/5320-01-024-
Fastener Length:
Between 0.302 inches and 0.322 inches
Head Style:
Undersized oval countersunk
Head Height:
Between 0.003 inches and 0.005 inches
Shank Diameter:
Between 0.093 inches and 0.096 inches
Shank Style:
Straight
Head Major Diameter:
Between 0.126 inches and 0.148 inches
Head Minor Diameter:
Between 0.086 inches and 0.096 inches
Countersink Height:
0.021 inches
Shear Strength:
261 single pounds per square inch
Countersink Angle:
100.0 degrees
Special Features:
Color violet
Heat Treatment:
T-73 solution heat treated
Material:
Aluminum alloy 7075
Material Specification:
Qq-a-430 federal specification single material response
Surface Treatment:
Chromate
Surface Treatment Specification:
Mil-c-5541 military specification single treatment response
Specification Data:
80205-nas1097 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
M-

No Fiig:

A040a0

NSN 5320-01-024-3399

Solid Rivet - Page 2 of 2



Mil-std (military Standard):

Mil-c-5541 spec.