# NSN 5320-01-024-3400

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-024-3400

## Fastener Length:

Between 0.240 inches and 0.260 inches

## Head Style:

Undersized oval countersunk

# Head Height:

Between 0.003 inches and 0.005 inches

## Shank Diameter:

Between 0.124 inches and 0.127 inches

#### Shank Style:

Straight w/radius chamfered tip

## Head Major Diameter:

Between 0.174 inches and 0.196 inches

## Head Minor Diameter:

0.134 mils and 0.144 centimeters

## **Countersink Height:**

0.029 inches

## Shear Strength:

468 single pounds per square inch

## Countersink Angle:

100.0 degrees

## Heat Treatment:

T-73 solution heat treated

## Material:

Aluminum alloy 7050

## **Material Specification:**

Qq-a-430 federal specification single material response

#### Surface Treatment:

Chromate

## Surface Treatment Specification:

Mil-c-5541 military specification single treatment response

## **Specification Data:**

80205-nas1097 professional/industrial association standard

#### Shelf Life:

N/a

# Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A040a0

## Mil-std (military Standard):

Mil-c-5541 spec.