NSN 5320-01-024-3403

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-024-3403

view Offiline at https://aerobasegroup.com/hsn/3320-01-024-0
Fastener Length:
Between 0.428 inches and 0.448 inches
Head Style:
Undersized oval countersunk
Head Height:
Between 0.003 inches and 0.005 inches
Shank Diameter:
Between 0.155 inches and 0.158 inches
Shank Style:
Straight
Head Major Diameter:
Between 0.225 inches and 0.247 inches
Head Minor Diameter:
Between 0.185 inches and 0.195 inches
Countersink Height:
0.037 inches
Shear Strength:
715 single pounds per square inch
Countersink Angle:
100.0 degrees
Heat Treatment:
T-73 solution heat treated
Material:
Aluminum alloy 7050
Material Specification:
Qq-a-430 federal specification single material response
Surface Treatment:
Chromate
Surface Treatment Specification:
Mil-c-5541 military specification single treatment response
Specification Data:
80205-nas1097 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-c-5541 spec.

Mil-std (military Standard):

A040a0