## NSN 5320-01-025-1807

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-025-1807

view Online at https://derobasegroup.com/nsi//0020-01-020-1007
Fastener Length:
Between 0.990 inches and 1.010 inches
Head Style:
Undersized oval countersunk
Head Height:
Between 0.003 inches and 0.005 inches
Shank Diameter:
Between 0.124 inches and 0.127 inches
Shank Style:
Straight w/radius chamfered tip
Head Major Diameter:
Between 0.1739 inches and 0.1957 inches
Head Minor Diameter:
0.134 mils and 0.144 centimeters
Countersink Height:
0.0286 inches
Countersink Angle:
100.0 degrees
Heat Treatment:
T-73 solution heat treated
Material:
Aluminum alloy 7050
Material Specification:
Qq-a-430, temper t73 federal specification single material response
Surface Treatment:
Chromate
Surface Treatment Specification:
Mil-c-5541, cl 1a military specification single treatment response
Specification Data:
80205-nas1097 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0

Mil-c-5541 spec.

Mil-std (military Standard):