# NSN 5320-01-025-1808

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-025-1808

## Fastener Length:

Between 1.490 inches and 1.510 inches

## Head Style:

Undersized oval countersunk

## Head Height:

Between 0.003 inches and 0.005 inches

## Shank Diameter:

Between 0.124 inches and 0.127 inches

#### Shank Style:

Straight w/radius chamfered tip

### Head Major Diameter:

Between 0.1739 inches and 0.1957 inches

### Head Minor Diameter:

0.134 mils and 0.144 centimeters

### **Countersink Height:**

0.0286 inches

## **Countersink Angle:**

100.0 degrees

## Heat Treatment:

T-73 solution heat treated

## Material:

Aluminum alloy 7050

## **Material Specification:**

Qq-a-430, temper t73 federal specification single material response

### Surface Treatment:

Chromate

## Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

### **Specification Data:**

80205-nas1097 professional/industrial association standard

### Shelf Life:

N/a

## Unit Of Measure:

--

### Demilitarization:

No

## Fiig:

A040a0

## Mil-std (military Standard):

Mil-c-5541 spec.