
# NSN 5320-01-026-0854

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.490 inches and 1.510 inches

### Head Style:

Err-090

#### Head Height:

Between 0.068 inches and 0.078 inches

### Width Between Flats:

Between 0.1270 inches and 0.1295 inches

#### Shank Diameter:

Between 0.311 inches and 0.312 inches

#### Shank Style:

Pin-rivet, straight, threaded

### Head Major Diameter:

Between 0.475 inches and 0.505 inches

## Lubrication:

Cetyl alcohol

## Grip Length:

1.005 inches

## Thready Qty Per Inch (tpi):

24

## Thread Size:

0.312 inches

## Shear Strength:

95000 single pounds per square inch

# Material:

Titanium alloy

# Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

## Surface Treatment:

Aluminum

# Surface Treatment Specification:

294, fscm 73197 mfr ref single treatment response

# **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-026-0854

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

