

View Online at <https://aerobasegroup.com/nsn/5320-01-026-0969>

**Fastener Length:**

0.576 inches

**Head Style:**

Undercut pan no. 2

**Head Height:**

Between 0.067 inches and 0.077 inches

**Shank Diameter:**

Between 0.155 inches and 0.159 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.296 inches and 0.328 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.376 inches and 0.437 inches

**Shear Strength:**

596 single pounds per square inch

**Heat Treatment:**

H-38 strain hardened locking ring

**Material:**

Aluminum alloy 5056 locking ring

**Material Specification:**

Qq-a-430 federal specification single material response locking ring

**Surface Treatment:**

Anodize or chromate

**Surface Treatment Specification:**

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

**Specification Data:**

80205-nas1398 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.