

View Online at <https://aerobasegroup.com/nsn/5320-01-027-9115>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

0.971 inches

Head Style:

Err-090

Head Height:

0.091 inches

Width Between Flats:

0.1582 inches

Shank Diameter:

0.3745 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

0.587 inches

Grip Length:

0.414 inches

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.375 inches

Shear Strength:

7000 single pounds per square inch

Special Features:

Head chamfered 50 deg, alum self-locking collar furnished

Heat Treatment:

As fabricated

Material:

Steel comp 4140 or steel comp 8740 or steel comp 4130

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6758 military specification 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.