

View Online at <https://aerobasegroup.com/nsn/5320-01-027-9115>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

0.971 inches

**Head Style:**

Err-090

**Head Height:**

0.091 inches

**Width Between Flats:**

0.1582 inches

**Shank Diameter:**

0.3745 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

0.587 inches

**Grip Length:**

0.414 inches

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.375 inches

**Shear Strength:**

7000 single pounds per square inch

**Special Features:**

Head chamfered 50 deg, alum self-locking collar furnished

**Heat Treatment:**

As fabricated

**Material:**

Steel comp 4140 or steel comp 8740 or steel comp 4130

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6758 military specification 3rd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5626 spec.