

View Online at <https://aerobasegroup.com/nsn/5320-01-029-8205>

Fastener Length:

Between 0.409 inches and 0.439 inches

Head Style:

Universal

Head Height:

Between 0.030 inches and 0.040 inches

Shank Diameter:

Between 0.124 inches and 0.128 inches

Head Major Diameter:

Between 0.238 inches and 0.262 inches

Expansion Device:

Plain stem-type t

Grip Length:

Between 0.251 inches and 0.312 inches

Shear Strength:

200 single pounds per square inch

Material:

Steel comp 1006 mandrel or steel comp 1008 mandrel or steel comp 1009 mandrel or steel comp 1010 mandrel or steel comp 1012 mandrel or steel comp 1015 mandrel or steel comp 1016 mandrel or steel comp 1017 mandrel or steel comp 1018 mandrel or steel comp 1019 mandrel or steel comp 1020 mandrel or steel comp 1021 mandrel or steel comp 1022 mandrel or steel comp 1023 mandrel or steel comp 1524 mandrel or steel comp 1025 mandrel

Material Specification:

Qq-a-430 federal specification single material response body

Surface Treatment:

Zinc mandrel or chromate mandrel or phosphate mandrel

Surface Treatment Specification:

Qq-z-325 type 2 cl 3 federal specification 1st treatment response mandrel or qq-p-416 federal specification 2nd treatment response mandrel or mil-p-16232 ty z cl 2 military specification 3rd treatment response mandrel or mil-p-16232 ty z cl 4 military specification 3rd treatment response mandrel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.