# NSN 5320-01-032-3027

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-032-3027

#### **Thread Class:**

3b

# **Thread Direction:**

Right-hand

## Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

## Shank Diameter:

Between 0.527 inches and 0.530 inches

#### Shank Style:

Blind rivet, nut and bolt (assembly)

#### Head Major Diameter:

0.535 inches

#### **Expansion Device:**

Threaded sleeve

#### Grip Length:

Between 0.178 inches and 0.198 inches

#### Thready Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Countersink Angle:

Between 98.0 degrees and 102.0 degrees

### **Special Features:**

Furnished without bolt

# Heat Treatment:

Annealed sleeve

Material:

Steel comp 303 expander

#### Material Specification:

Qq-a-430 federal specification single material response sleeve

#### Surface Treatment:

Cadmium expander

#### Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response expander

#### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

### Unit Of Measure:

--

### Demilitarization:

No

# NSN 5320-01-032-3027

Blind Rivet - Page 2 of 2

Fiig: A040a0

Mil-std (military Standard):

Mil-a-8625 spec.

