
## NSN 5320-01-032-3030

Blind Rivet - Page 1 of 2



# AeroBas Gro

#### **Thread Class:**

3b

#### **Thread Direction:**

Right-hand

#### Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

#### Shank Diameter:

0.387 inches

#### Shank Style:

Blind rivet, nut and bolt (assembly)

#### Head Major Diameter:

0.450 inches

#### **Expansion Device:**

Threaded sleeve

#### Grip Length:

#### 0.062 inches

Thready Qty Per Inch (tpi):

28

#### Thread Size:

0.250 inches

#### **Countersink Angle:**

Between 98.0 degrees and 102.0 degrees

#### **Special Features:**

Furnished without bolt, 1.438 in. Lg expander

#### Material:

Steel comp 303 expander

#### Material Specification:

Qq-a-430 federal specification single material response sleeve

#### Surface Treatment:

Cadmium expander

#### Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response expander

#### **Thread Series Designator:**

Unjf

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A040a0

## NSN 5320-01-032-3030

Blind Rivet - Page 2 of 2

### Mil-std (military Standard):

Mil-a-8625 spec.

