# NSN 5320-01-032-8075

Blind Rivet - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5320-01-032-8075

# Thread Class:

3b

# **Thread Direction:**

Right-hand

# Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

# Shank Diameter:

Between 0.309 inches and 0.312 inches

#### Shank Style:

Blind rivet, nut and bolt (assembly)

# Head Major Diameter:

0.372 inches

#### **Expansion Device:**

Threaded sleeve

#### Grip Length:

Between 0.240 inches and 0.260 inches

### Thready Qty Per Inch (tpi):

32

# **Thread Size:**

0.190 inches

# Countersink Angle:

Between 98.0 degrees and 102.0 degrees

### **Special Features:**

Furnished without bolt

# Heat Treatment:

Annealed sleeve

#### Material:

Steel comp 303 expander

### **Material Specification:**

Qq-a-430 federal specification single material response sleeve

### Surface Treatment:

Anodize sleeve

### Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response stem

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

# NSN 5320-01-032-8075

Blind Rivet - Page 2 of 2

**Fiig:** A040a0

Mil-std (military Standard):

Mil-a-8625 spec.

