# NSN 5320-01-033-2736

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-033-2736

# Fastener Length:

0.787 inches

### Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

## Shank Diameter:

Between 0.186 inches and 0.190 inches

## Shank Style:

Self-plugging mechanically locked stem

## Head Major Diameter:

0.357 inches

#### Expansion Device:

Serrated stem-type w

#### Grip Length:

Between 0.563 inches and 0.625 inches

#### Shear Strength:

1090 single pounds per square inch

# **Countersink Angle:**

100.0 degrees

## Heat Treatment:

T-4 solution heat treated

# Material:

Aluminum alloy 2017 body

# Material Specification:

Qq-a-430 federal specification single material response stem

# Surface Treatment:

Anodize or chromate

# Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

# Specification Data:

80205-nas1399 professional/industrial association standard

#### Shelf Life:

N/a

# Unit Of Measure:

```
---
```

# Demilitarization:

No

Fiig:

A040a0

# Mil-std (military Standard):

Mil-a-8625 spec.