NSN 5320-01-033-8176

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-033-8176

View Online at https://aerobasegroup.com/nsn/5320-01-033-8176
Fastener Length:
Between 0.432 inches and 0.452 inches
Head Style:
Universal
Head Height:
Between 0.067 inches and 0.077 inches
Shank Diameter:
Between 0.173 inches and 0.176 inches
Shank Style:
Self-plugging mechanically locked stem
Head Major Diameter:
Between 0.296 inches and 0.328 inches
Expansion Device:
Serrated stem-type w
End Application:
Aircraft, hercules c-130; aircraft, phantom f-4; helicopter, green giant h-3; aircraft, eagle f-15; aircraft, f-111; aircraft, galaxy c-5;
aircraft, delta dart f-106; aircraft, ac-130h, mc-130h, ec-130e, hc-130); aircraft, starlifter c-141; helicopter, super jolly h-53
Grip Length:
Between 0.251 inches and 0.312 inches
Special Features:
Ns" letters after the material code "b" indicate no preference to lock type (may be visible or internal). Rivets with no letter code (indicating
visible lock type) and rivets with the letter "h" after the material code (indicating internal lock type) are both acceptable for this item of supply.
Material:
Steel comp 8740 stem
Material Specification:
Qq-a-430 federal specification single material response body
Surface Treatment:
Cadmium stem
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response stem
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):

Mil-c-5541 spec.