

View Online at <https://aerobasegroup.com/nsn/5320-01-033-8180>

Fastener Length:

Between 0.505 inches and 0.525 inches

Head Style:

Universal

Head Height:

Between 0.080 inches and 0.090 inches

Shank Diameter:

Between 0.202 inches and 0.205 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.356 inches and 0.394 inches

Expansion Device:

Serrated stem-type w

End Application:

Helicopter, super jolly h-53; helicopter, iroquois hh/uh-1; aircraft, thunderbolt ii, a-10; aircraft, eagle f-15; aircraft, f-111; aircraft, galaxy c-5; aircraft, phantom f-4; aircraft, hercules c-130; aircraft, ac-130h, mc-130h, ec-130e, hc-130); aircraft, delta dart f-106

Grip Length:

Between 0.313 inches and 0.375 inches

Special Features:

Ns" letters after the material code "b" indicate no preference to lock type (may be visible or internal). Rivets with no letter code (indicating visible lock type) and rivets with the letter "h" after the material code (indicating internal lock type) are both acceptable for this item of supply.

Material:

Steel comp 8740 stem

Material Specification:

Qq-a-430 federal specification single material response body

Surface Treatment:

Cadmium stem

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-c-5541 spec.