## NSN 5320-01-033-8181

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-033-8181

| Fastener Length:   |
|--|
| Between 0.443 inches and 0.463 inches  |
| Head Style:  |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)   |
| Shank Diameter:  |
| Between 0.202 inches and 0.205 inches  |
| Shank Style:   |
| Self-plugging mechanically locked stem   |
| Head Major Diameter:   |
| 0.353 inches   |
| Expansion Device:  |
| Serrated stem-type w   |
| Grip Length:   |
| Between 0.251 inches and 0.312 inches  |
| Countersink Angle:   |
| 100.0 degrees  |
| Special Features:  |
| Ns" letters after the material code "b" indicate no preference to lock type (may be visible or internal). Rivets with no letter code (indicating       |
| visible lock type) and rivets with the letter "h" after the material code (indicating internal lock type) are both acceptable for this item of supply. |
| Material:  |
| Steel comp 8740 stem   |
| Material Specification:  |
| Qq-a-430 federal specification single material response body   |
| Surface Treatment:   |
| Cadmium stem   |
| Surface Treatment Specification:   |
| Qq-p-416, type 2, cl 3 federal specification single treatment response stem  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A040a0   |
| Mil-std (military Standard):   |
| Mil-c-5541 spec.   |