

View Online at <https://aerobasegroup.com/nsn/5320-01-033-8641>

**Fastener Length:**

Between 0.160 inches and 0.180 inches

**Head Style:**

Universal

**Head Height:**

Between 0.054 inches and 0.064 inches

**Shank Diameter:**

Between 0.140 inches and 0.143 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.238 inches and 0.262 inches

**Expansion Device:**

Serrated stem-type w

**End Application:**

Engine, aircraft, tf-33-p-7 (c-141a/b); aircraft, ac-130h, mc-130h, ec-130e, hc-130; helicopter, search and rescue, hh-60h; helicopter, uscg search and rescue, hh-60j; aircraft, phantom f-4; helicopter, carrier based asw, sh-60f; joint stars target radar system; helicopter, electronic countermeasures, eh-60a; aircraft mh-47e special operations aircraft

**Grip Length:**

Between 0.020 inches and 0.062 inches

**Special Features:**

Ns" letters after the material code "b" indicate no preference to lock type (may be visible or internal). Rivets with no letter code (indicating visible lock type) and rivets with the letter "h" after the material code (indicating internal lock type) are both acceptable for this item of supply.

**Material:**

Steel comp 8740 stem

**Material Specification:**

Qq-a-430 federal specification single material response body

**Surface Treatment:**

Cadmium stem

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response stem

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-c-5541 spec.