

View Online at <https://aerobasegroup.com/nsn/5320-01-033-8643>

Fastener Length:

Between 0.255 inches and 0.275 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.202 inches and 0.205 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

0.270 inches

Expansion Device:

Serrated stem-type w

End Application:

Aircraft, phantom f-4; aircraft, startofortress b-52; engine, aircraft, tf-33-p-7 (c-141a/b); engine, aircraft, tf33-pw-102 (c-135e, ec-135h/k/p) u-2 support equipment; truck, ambulance, 2-litter, soft top, 1 1/4 ton hmwv; aircraft, ac-130h, mc-130h, ec-130e, hc-130); helicopter, iroquois uh-1; truck, utility, cargo troop carrier, 5/4-ton w/e (m998); helicopter, sof / hh-53h pave low

Grip Length:

Between 0.063 inches and 0.125 inches

Countersink Angle:

100.0 degrees

Special Features:

Ns" letters after the material code "b" indicate no preference to lock type (may be visible or internal). Rivets with no letter code (indicating visible lock type) and rivets with the letter "h" after the material code (indicating internal lock type) are both acceptable for this item of supply.

Material:

Steel comp 8740 stem

Material Specification:

Qq-a-430 federal specification single material response body

Surface Treatment:

Cadmium stem

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-c-5541 spec.