

View Online at <https://aerobasegroup.com/nsn/5320-01-033-9125>

Fastener Length:

Between 0.255 inches and 0.275 inches

Head Style:

Universal

Head Height:

Between 0.080 inches and 0.090 inches

Shank Diameter:

Between 0.202 inches and 0.205 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.356 inches and 0.394 inches

Expansion Device:

Serrated stem-type w

End Application:

Aircraft, b-2 bomber (atb); aircraft, phantom f-4; aircraft, stratofortress b-52; engine, aircraft, tf-33-p-7 (c-141a/b); aircraft, stratolifter c-135; aircraft, delta dart f-106; helicopter, iroquois uh-1; aircraft, ac-130h, mc-130h, ec-130e, hc-130); u-2 support equipment; aircraft, hercules c-130

Grip Length:

Between 0.063 inches and 0.125 inches

Special Features:

Ns" letters after the material code "b" indicate no preference to lock type (may be visible or internal). Rivets with no letter code (indicating visible lock type) and rivets with the letter "h" after the material code (indicating internal lock type) are both acceptable for this item of supply.

Material:

Steel comp 8740 stem

Material Specification:

Qq-a-430 federal specification single material response body

Surface Treatment:

Cadmium stem

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-c-5541 spec.