

View Online at <https://aerobasegroup.com/nsn/5320-01-033-9125>

**Fastener Length:**

Between 0.255 inches and 0.275 inches

**Head Style:**

Universal

**Head Height:**

Between 0.080 inches and 0.090 inches

**Shank Diameter:**

Between 0.202 inches and 0.205 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.356 inches and 0.394 inches

**Expansion Device:**

Serrated stem-type w

**End Application:**

Aircraft, b-2 bomber (atb); aircraft, phantom f-4; aircraft, stratofortress b-52; engine, aircraft, tf-33-p-7 (c-141a/b); aircraft, stratolifter c-135; aircraft, delta dart f-106; helicopter, iroquois uh-1; aircraft, ac-130h, mc-130h, ec-130e, hc-130); u-2 support equipment; aircraft, hercules c-130

**Grip Length:**

Between 0.063 inches and 0.125 inches

**Special Features:**

Ns" letters after the material code "b" indicate no preference to lock type (may be visible or internal). Rivets with no letter code (indicating visible lock type) and rivets with the letter "h" after the material code (indicating internal lock type) are both acceptable for this item of supply.

**Material:**

Steel comp 8740 stem

**Material Specification:**

Qq-a-430 federal specification single material response body

**Surface Treatment:**

Cadmium stem

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response stem

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-c-5541 spec.