NSN 5320-01-033-9661

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-033-9661 **Thread Class:** 3b **Thread Direction:** Right-hand **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.387 inches and 0.390 inches **Shank Style:** Blind rivet, nut and bolt (assembly) **Head Major Diameter:** 0.7604 inches **Expansion Device:** Threaded sleeve **Grip Length:** 0.875 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp 305 sleeve **Material Specification:** Qq-s-763 federal specification single material response sleeve **Surface Treatment:** Cadmium sleeve **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response sleeve **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A040a0

NSN 5320-01-033-9661

Blind Rivet - Page 2 of 2



Mil-std (military Standard):

Mil-s-18732 spec.