

View Online at <https://aerobasegroup.com/nsn/5320-01-034-1886>

Fastener Length:

Between 0.393 inches and 0.413 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.140 inches and 0.143 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

0.211 inches

Expansion Device:

Serrated stem-type w

End Application:

Aircraft, delta dart f-106; aircraft, phantom f-4; aircraft, galaxy c-5; aircraft, f-111; aircraft, ac-130h, mc-130h, ec-130e, hc-130); aircraft, starlifter c-141; helicopter, super jolly h-53; aircraft, hercules c-130; aircraircraft, eagle f-15; helicopter, iroquois hh/uh-1

Grip Length:

Between 0.251 inches and 0.312 inches

Countersink Angle:

100.0 degrees

Special Features:

Ns" letters after the material code "b" indicate no preference to lock type (may be visible or internal). Rivets with no letter code (indicating visible lock type) and rivets with the letter "h" after the material code (indicating internal lock type) are both acceptable for this item of supply.

Material:

Steel comp 8740 stem

Material Specification:

Qq-a-430 federal specification single material response body

Surface Treatment:

Cadmium stem

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-c-5541 spec.