

View Online at <https://aerobasegroup.com/nsn/5320-01-034-2846>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.877 inches and 0.897 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.055 inches and 0.074 inches

**Width Between Flats:**

Between 0.079 inches and 0.081 inches

**Shank Diameter:**

Between 0.1885 inches and 0.1895 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.295 inches and 0.315 inches

**Grip Length:**

0.567 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Shear Strength:**

2540 double pounds per square inch

**Heat Treatment:**

T-6 solution heat treated

**Material:**

Aluminum alloy 7075

**Material Specification:**

Qq-a-225/9 federal specification 1st material response or qq-a-430 federal specification 2nd material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-a-8625 spec.