NSN 5320-01-035-4331

View Online at https://aerobasegroup.com/nsn/5320-01-035-4331

Pin-rivet - Page 1 of 2



Thread Class: За **Thread Direction:** Right-hand Fastener Length: Between 1.800 inches and 1.820 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.2207 inches and 0.2242 inches **Shank Diameter:** Between 0.4985 inches and 0.4995 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.754 inches Lubrication: Cetyl alcohol **Grip Length:** 1.135 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch **Thread Size:** 0.500 inches **Shear Strength:** 132000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Nas672 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5320-01-035-4331

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0