# NSN 5320-01-036-2823

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-036-2823

### Thread Class:

3b

## **Thread Direction:**

Right-hand

#### Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

## Shank Diameter:

Between 0.387 inches and 0.390 inches

#### Shank Style:

Blind rivet, nut and bolt (assembly)

#### Head Major Diameter:

0.7604 inches

#### **Expansion Device:**

Threaded sleeve

#### Grip Length:

# 0.625 inches

Thready Qty Per Inch (tpi):

28

#### Thread Size:

0.250 inches

#### Shear Strength:

125000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

#### Material:

Steel comp 305 sleeve

#### **Material Specification:**

Qq-s-763 federal specification single material response sleeve

#### Surface Treatment:

Cadmium sleeve

#### Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response sleeve

#### **Thread Series Designator:**

Unjf

#### Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A040a0

# NSN 5320-01-036-2823

Blind Rivet - Page 2 of 2

# Mil-std (military Standard):

Mil-s-18732 spec.

