# NSN 5320-01-036-4008

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-036-4008



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.885 inches and 0.905 inches

## Head Style:

Flush countersunk

### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

## Shank Diameter:

Between 0.2485 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.3898 inches and 0.3948 inches

#### Lubrication:

Cetyl alcohol

# Grip Length:

0.505 inches

## Thready Qty Per Inch (tpi):

28

## Thread Size:

0.250 inches

#### Shear Strength:

132000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

#### Material:

Steel comp h11

#### Material Specification:

Ams 6487 assn standard single material response

#### Surface Treatment:

Nickel and cadmium

#### **Surface Treatment Specification:**

Ams 2416 assn standard all treatment responses

#### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-036-4008

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

