## NSN 5320-01-036-7966

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-036-7966

| Fastener Length:   |
|--|
| 0.763 inches   |
| Head Style:  |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)   |
| Shank Diameter:  |
| Between 0.155 inches and 0.159 inches  |
| Shank Style:   |
| Self-plugging shank w/grooved end for locking  |
| Head Major Diameter:   |
| 0.290 inches   |
| Expansion Device:  |
| Serrated stem-type w   |
| Grip Length:   |
| Between 0.563 inches and 0.625 inches  |
| Countersink Angle:   |
| 100.0 degrees  |
| Material:  |
| Aluminum alloy 5056 locking ring   |
| Material Specification:  |
| Qq-a-430 federal specification single material response stem   |
| Surface Treatment:   |
| Anodize stem or chromate stem  |
| Surface Treatment Specification:   |
| Mil-a-8625 military specification 1st treatment response stem or mil-c-5541 military specification 2nd treatment response stem |
| Specification Data:  |
| 80205-nas1921 professional/industrial association standard   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A040a0   |
| Mil-std (military Standard):   |
| Mil-a-8625 spec.   |
|  |