NSN 5320-01-038-4265

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-038-4265 **Thread Class:** За **Thread Direction:** Left-hand Fastener Length: 0.652 inches **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.274 inches and 0.276 inches **Shank Style:** Threaded self-plugging shank w/sleeve **Head Major Diameter:** Between 0.463 inches and 0.507 inches **Expansion Device:** Threaded sleeve Lubrication: Grease film **Grip Length:** Between 0.220 inches and 0.281 inches Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.190 inches **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Heat Treatment:** Annealed sleeve Material: Steel comp 8740 nut **Material Specification:** Mil-s-6049 military specification single material response nut **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 type 1 cl 3 federal specification single treatment response sleeve **Thread Series Designator:** Unf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-038-4265

Blind Rivet - Page 2 of 2



Demi			

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6049 spec.