## NSN 5320-01-039-3954

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-039-3954 **Thread Class: Thread Direction:** Right-hand Fastener Length: Between 1.681 inches and 1.701 inches **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.254 inches and 0.257 inches **Shank Style:** Blind rivet, nut and bolt (assembly) **Head Major Diameter:** Between 0.3256 inches and 0.3304 inches **Expansion Device:** Threaded sleeve **Grip Length:** 1.375 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp 305 sleeve **Material Specification:** Qq-s-763 federal specification single material response sleeve **Surface Treatment:** Cadmium sleeve **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response sleeve **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5320-01-039-3954

Blind Rivet - Page 2 of 2



Fiig:

A040a0

Mil-std (military Standard):

Mil-a-18732 spec.