

View Online at <https://aerobasegroup.com/nsn/5320-01-040-4810>

**Fastener Length:**

Between 0.455 inches and 0.475 inches

**Head Style:**

Universal

**Head Height:**

Between 0.054 inches and 0.064 inches

**Shank Diameter:**

Between 0.140 inches and 0.143 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.238 inches and 0.262 inches

**Expansion Device:**

Serrated stem-type w

**End Application:**

Helicopter, advance attack, ah-1w; aircraft, phantom f-4; engine, aircraft, tf-33-p-7 (c-141a/b); aircraft, delta dart f-106; aircraft, stratofortress b-52; aircraft, ac-130h, mc-130h, ec-130e, hc-130; aircraft, stratolifter c-135; aircraft, f-111; aircraft, hercules c-130; helicopter observation (ahip), oh-58d

**Grip Length:**

Between 0.313 inches and 0.375 inches

**Special Features:**

Ns" letters after the material code "b" indicate no preference to lock type (may be visible or internal). Rivets with no letter code (indicating visible lock type) and rivets with the letter "h" after the material code (indicating internal lock type) are both acceptable for this item of supply.

**Material:**

Steel comp 8740 stem

**Material Specification:**

Qq-a-430 federal specification single material response body

**Surface Treatment:**

Cadmium stem

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response stem

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-c-5541 spec.