NSN 5320-01-040-8051

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-040-8051

Thread Class:
3b
Thread Direction:
Right-hand
Fastener Length:
Any acceptable
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.254 inches and 0.257 inches
Shank Style:
Blind rivet, nut and bolt (assembly)
Head Major Diameter:
0.5066 inches
Expansion Device:
Threaded sleeve
Fluid Tight Seal Type:
Sleeve
Grip Length:
Between 1.302 inches and 1.322 inches
Thready Qty Per Inch (tpi):
32
Thread Size:
0.164 inches
Shear Strength:
125000 single pounds per square inch
Countersink Angle:
100.0 degrees
Seal Material:
Rubber synthetic
Material:
Steel comp 305 sleeve
Material Specification:
Qq-s-763 federal specification single material response sleeve
Surface Treatment:
Cadmium sleeve
Surface Treatment Specification:
Qq-p-416, type 1, cl 3 federal specification single treatment response sleeve
Thread Series Designator:
Unjc
Shelf Life:
N/a

NSN 5320-01-040-8051

Blind Rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-18732 spec.

