## NSN 5320-01-040-8059

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-040-8059
Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Bronze
Fastener Length:
Between 2.035 inches and 2.055 inches
Head Style:
Err-090
Head Height:
Between 0.078 inches and 0.088 inches
Width Between Flats:
Between 0.1582 inches and 0.1617 inches
Shank Diameter:
Between 0.3735 inches and 0.3745 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.565 inches and 0.600 inches
Grip Length:
1.505 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Thread Size:
0.375 inches
Shear Strength:
95000 single pounds per square inch
Special Features:
Color bronze, cetyl alcohol lubrication
Material:
Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740
Material Specification:
Mil-s-5000 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-5626 military
specification 3rd material response or mil-s-6049 military specification 4th material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response

Unjf

**Thread Series Designator:** 

## NSN 5320-01-040-8059

Pin-rivet - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:

Shelf Life:

Fiig:

No

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.