

View Online at <https://aerobasegroup.com/nsn/5320-01-043-0068>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.363 inches and 1.383 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.103 inches and 0.115 inches

**Width Between Flats:**

Between 0.2207 inches and 0.2242 inches

**Shank Diameter:**

Between 0.4985 inches and 0.4995 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.735 inches and 0.770 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

0.693 inches

**Thready Qty Per Inch (tpi):**

20

**Thread Size:**

0.500 inches

**Shear Strength:**

125000 single pounds per square inch

**Material:**

Steel comp 431 or steel comp 431

**Material Specification:**

Ms5628 assn standard single material response or mil-s-18732 type 431 military specification 1st material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0

**Mil-std (military Standard):**

Mil-s-18732 spec.