## NSN 5320-01-043-1928

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-043-1928

<b>Fastener</b>	I an	ath:
rastener	Len	uuı.

Between 0.404 inches and 0.434 inches

**Head Style:** 

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:** 

Between 0.172 inches and 0.176 inches

**Shank Style:** 

Self-plugging mechanically locked stem

**Head Major Diameter:** 

Between 0.282 inches and 0.290 inches

**Expansion Device:** 

Serrated stem-type w

**End Application:** 

Aircraft, phantom f-4; aircraft, eagle f-15; aircraft, galaxy c-5; aircraft, b-1b; aircraft, stratofortress b-52; aircraft, thunderbolt ii, a-10; aircraft, f-111; aircraft, t-37; aircraft, hercules c-130; aircraft, ac-130h, mc-130h, ec-130e, hc-130

**Grip Length:** 

Between 0.251 inches and 0.312 inches

**Countersink Angle:** 

Between 98.5 degrees and 101.5 degrees

Material:

Steel comp 632 stem

**Material Specification:** 

Qq-n-281 federal specification all material responses sleeve

**Specification Data:** 

81349-mil-r-7885/9 government specification

**Specification Or Standard:** 

1 type and b style and 2 class

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A040a0