# NSN 5320-01-043-1935

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-043-1935

Fa	Sta	ner	م ا	natl	h.
ıa	315	HEI	ᆫ	เเนเ	и.

Between 0.691 inches and 0.621 inches

# **Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

#### **Shank Diameter:**

Between 0.172 inches and 0.176 inches

# **Shank Style:**

Self-plugging mechanically locked stem

# **Head Major Diameter:**

Between 0.282 inches and 0.290 inches

# **Expansion Device:**

Serrated stem-type w

# **End Application:**

Ws: aircraft, f-111; aircraft, thunderbolt ii, a-10; aircraft, b-1b; aircraft, stratofortress b-52; aircraft, phantom f-4; aircraft, eagle f-15; aircraft, sf (ac-130h, mc-130h, ec-130e, hc-130)

# **Grip Length:**

Between 0.438 inches and 0.500 inches

# **Countersink Angle:**

Between 98.5 degrees and 101.5 degrees

#### Material:

Steel comp 632 stem

# **Material Specification:**

Qq-n-281 federal specification all material responses sleeve

# **Specification Data:**

81349-mil-r-7885/9 government specification

# **Specification Or Standard:**

1 type and b style and 2 class

# Shelf Life:

N/a

#### **Unit Of Measure:**

# **Demilitarization:**

No

# Fiig:

A040a0