# NSN 5320-01-043-1936

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-043-1936



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 1.097 inches and 1.117 inches

# Head Style:

Err-090

#### Head Height:

Between 0.078 inches and 0.088 inches

#### Width Between Flats:

Between 0.1582 inches and 0.1617 inches

#### Shank Diameter:

Between 0.3735 inches and 0.3745 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.565 inches and 0.600 inches

Lubrication:

Cetyl alcohol

Grip Length:

0.567 inches

## Thready Qty Per Inch (tpi):

24

#### Min. Tensile Strength (psi):

260000 pounds per square inch

#### **Thread Size:**

0.375 inches

#### Shear Strength:

156000 single pounds per square inch

#### Material:

Steel comp h11

#### **Material Specification:**

Ams 6487 assn standard single material response

#### Surface Treatment:

Nickel and cadmium

## Surface Treatment Specification:

Ams 2416 assn standard all treatment responses

# **Thread Series Designator:**

Unjf

#### Shelf Life:

N/a

# NSN 5320-01-043-1936

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

