NSN 5320-01-043-5866

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-043-5866

Fastener Length:
Between 0.380 inches and 0.400 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.201 inches and 0.205 inches
Shank Style:
Self-plugging mechanically locked stem
Head Major Diameter:
0.357 inches
Expansion Device:
Serrated stem-type w
Lubrication:
Dry film
End Application:
9helicopter, cobra/tow, ah series; aircraft, ac-130h, mc-130h, ec-130; aircraft, phantom f-4; aircraft, f-111; aircraft, b-1b; aircraft, eagle
f-15; aircraft, stratofortress b-52; helicopter, uh-60a/uh-60d; aircraft, galaxy c-5; airctaft, thunderbolt ii, a-10
Grip Length:
Between 0.188 inches and 0.250 inches
Countersink Angle:
100.0 degrees
Special Features:
Lubrication on stem only
Material:
Steel comp 632 stem
Material Specification:
Qq-n-281 federal specification all material responses body
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0